

ABBAcoat-Primer

Ready-to-use product

▶ **Undercoat for roof paint ABBAcoat
Surface stabiliser**

▶ DESTINATION

ABBAcoat-Primer is designed to stabilise chalky surfaces in order to ensure a good adherence of the **ABBAcoat** coating.

ABBAcoat-Primer is very easy to use, it is designed to add a better hold of paint onto materials which haven't got a firm enough surface for a direct application.

ABBAcoat-Primer can be applied with a brush after dusting on a basis of 1 litre for 3 to 5 m² depending on the porosity of the surfaces.

▶ PRESENTATION

ABBAcoat-Primer is an aqueous milky-white paint which has been specially designed to stabilise roof surfaces before the application of **ABBAcoat**.

ABBAcoat-Primer offers a high penetrating quality which allows to stabilise chalky surfaces.

ABBAcoat-Primer presents an excellent surface cohesion.

ABBAcoat-Primer offers a very fast drying time : paint can be applied just after three hours.

▶ HOW TO APPLY

ABBAcoat-Primer can be applied onto clean and dry surfaces.

ABBAcoat-Primer must always be applied when temperatures are above 5°C.

Also, avoid applying in very hot weather and when the surfaces are exposed to the sun.

It is advised to decontaminate the surface with **ABBAmousses** before applying **ABBAcoat-Primer**.

Avoid projection on the surfaces which are not meant for treatment (glass, metals, plastics ...) and protect them during the application. In the case of accidental projection, wipe off the product with a cloth or sponge and water.

▶ PACKAGING

- 5-litre bottle
- 10-litre bottle
- 25-litre drum

This document presents the main information regarding this product.
The detailed information sheet is available upon request.

Our technical service is at your disposal to advise you on this product

PRODUCTS
ABBA

1, rue du 11 Novembre - 85130 La Verrie
FRANCE

Tél. 00 33 + 2 51 65 95 46

Fax 00 33 + 2 41 75 89 08

www.abba-products.com