

Read-to-use product

► Undercoating for floor paint or stick materials

► DESTINATION

ABBafix is a grey single component primer designed to form an undercoating for floor painting. **ABBafix** has been designed to strengthen the adherence of special domestic or industrial floor paints.

ABBafix is the indispensable complement to aid resin-rich paints to reach better performances.

INSULATING these special paints from alkalinity of concrete, **ABBafix** create a link between the coat of paint and the surface in order to ensure lasting quality in time.

DURABLE, offers a better adherence of the coating on concrete.

PROVEN, **ABBafix** has been tested and approved on classic floor paint containing polyurethane resins, epoxy, alkyde-uréthane.

COST EFFECTIVE, no more need to apply a first coat of diluted paint which does not always give an effective and long lasting adherence. This reduces costs as experience has shown that one single coat applied on a smooth floor is sufficient for a moderate pedestrian traffic.

Reducing the cost of maintaining and paint consumption, **ABBafix** allows a cost effective floor painting which is usually considered expensive.

► OTHER SCOPES OF USAGE

ABBafix is also often used as anti-dust impregnator when applied in one or two coats onto concrete floors :

- with low lever pedestrian traffic
- as a temporary protection
- before laying adhesive floor tiles

ABBafix can be reapplied on itself as a maintaining process or before applying a classic floor paint.

► PRESENTATION

ABBafix is a special synthetic resin emulsion designed to impregnate concrete floors.

ABBafix offers high penetrating powers for an in-depth efficiency.

These characteristics are favourable for floor paints as it allows a better adherence and an easier and smoother application.

ABBafix prevents the coat of paint to flake off or to chip.

ABBafix offers the same advantages for the laying of adhesive materials (carpets, laminated floors, tiles, etc...).

▶ HOW TO APPLY

ABBAfix must be applied onto clean and dry concrete surfaces (should the surface present some stains, it is advised clean the surface with ; **ABBAcime** prior to using **ABBAfix**).

When applying to new, closed up floors, it is advised to take the glaze off the surface (Solution of 10% hydrochloric acid with water then rinse off).

ABBAfix can be applied with a brush, roll or paint gun in one single coat on a basis of 4 to 6 m² for 1 litre of water in a tick and sufficiently abundant coat.

In the case of high absorption of the product by the surface, a second application might be necessary. Allow 3 hours between applications.

Avoid projection on the surfaces which are not meant for treatment (glass, metals, plastics ...) and protect them during the applications.

In the case of accidental projection, wipe off the product with a cloth or sponge and water.

▶ APPLICATION TEST

If using **ABBAfix** for the first time with a certain type of paint, it is advised to carry out a compatibility test. If needed, this test can be carried out by our Technical Service for you* : a test tube and a test form will be posted to you free of charge.

▶ PACKAGING

Buckets

- 5 Kg

- 25 Kg

This document presents the main information regarding this product.
The detailed information sheet is available upon request.

Our technical service is at your disposal to advise you on this product

** For a compatibility test, please contact our agent
or telephone the head office directly on .:*

PRODUCTS
ABBA

1, rue du 11 Novembre - 85130 La Verrie
FRANCE

Tél. 00 33 + 2 51 65 95 46

Fax 00 33 + 2 41 75 89 08

www.abba-products.com