

► **Blocks out rising damp by capillary action in the walls**
Ready-to-use product

► DESTINATION

ABBAmur is designed to block out rising damp in the walls .

ABBAmur is a single component product which prevents humidity which rises from the ground to penetrate into the walls leading to the deterioration of the materials .

ABBAmur is injected in the lower part of the walls . The necessary quantity depends on the thickness and the composition of the wall . The consumption is measurable in linear metres and therefore it is variable .

► PRESENTATION

ABBAmur is an aqueous [méthylsiliconate de potassium]-based product .

ABBAmur is a liquid product which solidifies and reticulates once injected inside the walls .

Stable and durable by this modification, **ABBAmur** prevents rising humidity by its capillarity action in the walls .

► HOW TO APPLY

ABBAmur is injected in the lower part of the walls, always above the ground and/or the first floorboard .

A complete technical application manual details all the necessary and fundamental instructions to a successful operation .

Our Technical Service is at your disposal for any complementary information and explanation and for any operational work .

Please note : **ABBAmur** can stop rising humidity . The drying above this point will be obtained after a longer period of time .

► PACKAGING

- 2-litre bottle
- 10-litre bottle
- 25-litre drum

This document presents the main information regarding this product.
 The detailed information sheet is available upon request.

Our technical service is at your disposal to advise you on this product