

ABBA^{sol}

Water-Oilproofing

► For waterproofing and oil and grease proofing of porous surfaces, interior and exterior tiling

Ready-to-use product

DESTINATION

ABBA^{sol} Water-Oilproofing is a product resulting from the technical progression of **ABBA^{sol} Waterproof**

ABBA^{sol} Water-Oilproofing is an elaborated version of **ABBA^{sol} Waterproof** to which the oil and grease waterproofing function has been added, it offers an extra protection against oils and grease .

When applied onto porous surfaces, **ABBA^{sol} Water-Oilproofing** allows these surfaces to be oil and grease proofed and fights against the penetration of vegetal or mineral oils, or even other greases .

ABBA^{sol} Water-Oilproofing is very easy to use and it is an invisible product designed to protect tiling.

ABBA^{sol} Water-Oilproofing can be sprayed or brushed onto the surface on a basis of 1 litre for approximately 3 to 5 m² depending on the absorption level of the materials .

SCOPE OF USAGE

ABBA^{sol} Water-Oilproofing can be use onto all porous tiling surfaces : Terracotta, Paving stones, Natural or tinted concrete, Natural or processed stones... . It is obvious that tiles which are naturally waterproof do not require this treatment .

PRESENTATION

ABBA^{sol} Water-Oilproofing is a product containing solvent and is without any side effects for the materials onto which it is applied .

ABBA^{sol} Water-Oilproofing protects materials without modifying their aspect : no formation of film, no consequences on their structure, no alteration of their colour .

The treatment of **ABBA^{sol} Water-Oilproofing** is completely invisible and the surfaces retain their original appearance once dry .

ABBA^{sol} Water-Oilproofing lets the materials breathe .

ABBA^{sol} Water-Oilproofing can be reapplied .

Surfaces treated with **ABBA^{sol} Water-Oilproofing** do not absorb oils immediately : oils and grease can be wiped off hours or even days after an accidental spillage, before penetrating the material .Strong spillage or pressure may result in oils penetrating the material through the treatment protection.

HOW TO APPLY

ABBA^{sol} Water-Oilproofing must always be applied onto clean and dry surfaces (if necessary previously decontaminated with **ABBA^{sol}**), with no risks of rain for at least half a day .

ABBA^{sol} Water-Oilproofing can easily be applied with a spray or a brush in a single thorough application without any excess . Avoid projection onto other surfaces which are not meant to be treated such as glass, plastic , metal, bitumen coating, etc ... These must be protected . In the case of projection onto non-absorbent material, wipe off immediately with a tissue and white spirit .

PACKAGING

- 2-litre bottle, 10-litre bottle, 25- litre drum

This document presents the main information regarding this product.
The detailed information sheet is available upon request.

Our technical service is at your disposal to advise you on this product

PRODUCTS
ABBA

1, rue du 11 Novembre - 85130 La Verrie
FRANCE

Tél. 00 33 + 2 51 65 95 46

Fax 00 33 + 2 41 75 89 08

www.abba-products.com